



20-YEAR GALVALUME® WARRANTY

Metal Roofing Center & Supply (*aka MRCS*) guarantees that roofing and siding panels made from hot dipped aluminum-zinc alloy coated Galvalume® sheet steel, if erected within the continental United States (which includes Alaska and Canada), **will not** rupture, fail structurally, or perforate within a period of twenty (20) years after shipment from our manufacturing branch due to exposure to normal atmospheric corrosion.

This warranty **does not apply** to sheets exposed at any time to corrosive, aggressive, harmful, or other abnormal weather or atmospheric conditions including but not limited to the conditions present in the following areas or circumstances:

- a. Areas subject to salt water, marine atmospheres, or repeated salt spray.
- b. Areas subject to fallout of, or exposure to corrosive chemicals, ash, fumes, dust (including cement dust), vapors, animal waste and confinement or other similar items.
- c. Areas subject to water run-off from lead or copper flashings or piping or areas in metallic contact with lead or copper.
- d. Areas subject to foreign substances, such as sand or dirt particles or other abrasive particles or other abrasive particles or substances.
- e. Circumstances where corrosive fumes or condensates are generated or released inside the building.
- f. Circumstances where, due to roof or sidewall pitch, there is improper drainage or holding of water.

This warranty **does not apply** in the event of:

- a. Bends less than 2T for sheet thickness 0.030 and thinner and less than 4T for sheet thickness 0.031 and thicker.
- b. Slopes of the roof or sections of the roof flatter than 1/4:12.
- c. Mechanical, chemical or other damage sustained during shipment, storage, or forming fabrication, or during or after erection, including without limitation damage caused by falling objects, acts of God, fire, riots, explosions, acts of war, or other external forces.
- d. Forming which incorporates stretching or severe reverse bending or which subjects coating to alternate compression and tension.
- e. Improper fabrication, embossing or cut edge exposure.
- f. Failure to provide free drainage of water, including internal condensation, from overlaps and all other surfaces of the sheets and panels.
- g. Failure to remove debris from overlaps and all other surfaces of the sheets and panels.
- h. Deterioration of the panels caused by contact with green or wet lumber or wet storage stain caused by water damage or condensation.
- i. Presence of damp insulation or other corrosive materials in contact with or close proximity to the panel.
- j. Deterioration of the panels caused directly or indirectly by panel contact with fasteners. The responsibility for the selection of suitable, long-lasting fasteners, to be used with the panels, rests solely with the Buyer or building owner.

This warranty shall be subject to the stipulations, limitations, and conditions hereinafter set forth:

1. MRCS's liability for breach of this warranty shall be limited exclusively to the cost of either repairing nonconforming panels, or at MRCS's sole option, of furnishing FOB Buyer's location sufficient sheet replacement panels for the nonconforming panels.
2. MRCS shall not in any event be liable for the cost of labor expended by others on any nonconforming sheet or for any special, indirect or consequential damages to anyone by reason of the fact that such panels shall have been nonconforming.
3. Claims must be promptly reported in writing to MRCS and MRCS shall be given a reasonable opportunity to inspect the panels claimed to be nonconforming. Adequate identification of the material involved in the claim, including date of installation, MRCS invoice number, and Buyer must provide date of shipment.
4. Buyer shall exercise diligence in inspection of sheets as received from MRCS so as to mitigate repair or replacement.



**Metal Roofing Center
and Supply**

5. MRCS extends this warranty solely to the Buyer. This warranty is non-transferable and non-assignable.
6. MRCS reserves the right to terminate this warranty at any time (except as to orders already accepted) upon the giving of written notice thereof.

MRCS makes no guarantees, either expressed or implied beyond the fact hereof: including, without limitations, warranties or fitness and merchantability and shall have no other liability with respect thereto.

Appendix A

For purposes of determining whether an exposed sheet meets the standards set forth above, all chalk, dirt and other film deposits on the area of the sheet to be tested for color must be removed by washing prior to evaluation.

To wash the test area, use a pad of 28/24 mesh cheesecloth and distilled water and a mild detergent cleaner. Wet the cheesecloth thoroughly with the cleaning solution and rub it, using moderate hand pressure, over an area of the sheet approximately 4"x4" Care must be taken to avoid any scratching, burnishing or other physical alteration of the coated surfaces.

After washing, as described above, flush off the test area with distilled water and allow to air-dry.

Failure to keep condensation or moisture from nested materials may result in damage or wet storage stain, voiding manufacturer's guarantee.

Project Name:

Project Address:

Owner Name:

Installer Name:

MRCS Invoice:

MRCS Rep. Signature:

Date: _____