



5 - V C R I M P

where OLD interlocks with NEW



SLOPE

3:12 (Minimum Recommended Slope)

SUBSTRATE

Only to be used over solid substrates. It is recommended to be installed over 5/8" plywood decking with a 30 pound felt moisture barrier.

COVERAGE

24" Coverage Panel, 1/2" Rib Height

LENGTH

MIN. 24", MAX 35'
(Longer lengths are available with prior coordination)

AVAILABILITY

26 and 24 Gauge

PERFORMANCE TEST

UL 580-94 / UL 1897-98 in accordance with Florida Building Code 2004.

FASTENING SYSTEM

Exposed Fastener # 10 – 12 x 6 x 1 1/2" HWH

MATERIALS

Steel Grade 50/E per ASTM A-792
Steel Grade 80/D per ASTM A-792

COLOR OPTIONS

Galvalume and Ceram-A-Star 1050 Stock Color - Kynar (available through special order)



A metal roof is more than just a pretty face. There are ways it can begin to pay off right away. Along with the peace-of-mind that comes from knowing your home is protected for a lifetime, energy efficient Cool Roof coatings can reduce your cooling costs as much as 30 percent. That's one reason why metal roofs such as 5-V Crimp panels are a simple yet beautiful solution to your residential roofing needs. 5-V Crimp's high strength steel and light colors will maintain its beauty for years to come. Best of all, the high strength and fire resistance of metal roofs *can result in lower home insurance premiums – with discounts up to 30 percent in some areas of the country!*

