



PBR PANEL

BEAUTIFUL & SMART

*prepare to be the talk
of the neighborhood*



SLOPE

1:12 (Minimum Recommended Slope)

SUBSTRATE

Open structure framing and solid substrates. It is recommended to be installed over 5/8" plywood decking with a 30 pound felt moisture barrier.

COVERAGE

36" Coverage Panel, 1 1/4" Rib Height

LENGTH

MIN. 36", MAX 40'
(Longer lengths are available with prior coordination)

AVAILABILITY

26 and 24 Gauge

PERFORMANCE TEST

UL 580-94 / UL 1897-98 in accordance with Florida Building Code 2004.

FASTENING SYSTEM

Exposed Fastener # 10 – 12 x 6 x 1 1/2" HWH

MATERIALS

Steel Grade 80/D per ASTM A-792

COLOR OPTIONS

Galvalume and Ceram-A-Star 1050 Stock Color - Kynar (available through special order)



Who says you can't combine beauty and brawn in a single package?

Our PBR Panel metal roofs are designed to provide optimum strength, which is ideal for maximum spanning capabilities, and the weather-tight side lap allows for applications on roof pitches as low as a 1:12. That's why metal roofs have become the material of choice among building owners, facility managers and architects alike. And you can forget those images of old, ugly metal roofs on grey barns. Our metal roofs are available in a wide variety of vivid colors that add lasting beauty and value to your home. **Once you have one, get ready to be the envy of your neighborhood!**

